


# DIN SMART SWITCH

## DALI CONTROLLED 8-AMP SWITCH



**COSINE DEVELOPMENTS**  
LEADERS IN LIGHTING TECHNOLOGY



### OVERVIEW:

- > Provides uncommitted 230 Vac 8A contacts
- > Enables switching of any load via the DALI link
- > Can be addressed via automatic addressing
- > Configurable via most DALI BMS systems
- > 5 year warranty on inverter

### PRODUCT DESCRIPTION:

The DIN SMART SWITCH is a DALI compatible digitally addressable lighting interface switch control unit. The DIN SMART SWITCH can switch a maximum load of 8A.

The unit complies with the Digital Addressable Lighting Interface (DALI) Standard IEC 62386 and is therefore compatible with all international interfaces. Its bi-directional bus uses standard protocol and can therefore be addressed by all reputable bridges.

#### This unit can be used to switch various items such as:

- > Air-conditioner switching
- > HID lamp control
- > Security gates operation
- > General lighting switching

SPECIFICATIONS	
<b>DALI Line Loading</b>	2mA (= one address)
<b>Dimensions</b> (L x W x H)	88 x 72 x 62mm
<b>Mains Current Consumption</b>	8mA
<b>Mains Voltage</b>	230V +/- 10%
<b>Maximum Ambient Temperature</b>	70°C
<b>Maximum Load</b>	8A